PATENT COOPERATION TREATY

PCT

REC'D	1	5	MAR	2006
WIPO				PCT

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

(Chapter II of the Patent Cooperation Treaty)

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference PD030135	FOR FURTHER A	ACTION	See Form PCT/IPEA/416					
International application No. PCT/EP2004/053448	International filing date 14.12.2004	(day/month/year)	Priority date (day/month/year) 18.12.2003					
International Patent Classification (IPC)	or national classification and	IPC						
G09G3/28, G06F1/035								
Applicant								
THOMSON LICENSING et al								
 This report is the international preliminary examination report, established by this International Preliminary Examining Authority under Article 35 and transmitted to the applicant according to Article 36. 								
2. This REPORT consists of a tot	al of 7 sheets, including	this cover sheet.						
3. This report is also accompanie		-						
		eau) a total of 8 sheets, a						
sheets of the description, claims and/or drawings which have been amended and are the basis of this report and/or sheets containing rectifications authorized by this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions).								
sheets which supersede earlier sheets, but which this Authority considers contain an amendment that goes beyond the disclosure in the international application as filed, as indicated in item 4 of Box No. I and the								
Supplemental Box. b. \(\simega \) (sent to the International	d Rureau only) a total of (i	indicate type and number	of algoritania apprior(a))					
b. (sent to the International Bureau only) a total of (indicate type and number of electronic carrier(s)), containing a sequence listing and/or tables related thereto, in computer readable form only, as indicated in the Supplemental Box Relating to Sequence Listing (see Section 802 of the Administrative Instructions).								
r .								
4. This report contains indications	4. This report contains indications relating to the following items:							
Box No. I Basis of the of th	ppinion							
☐ Box No. II Priority								
☐ Box No. III Non-establishment of opinion with regard to novelty, inventive step and			tep and industrial applicability					
☐ Box No. IV Lack of unity	of invention							
⊠ Box No. V Reasoned state applicability; applicability;	atement under Article 35(citations and explanations	2) with regard to novelty, is supporting such stateme	inventive step or industrial ent					
☐ Box No. VI Certain docui								
	Certain defects in the international application							
☐ Box No. VIII Certain obser	vations In the internation	al application						
Date of submission of the demand Date of completion of this report								
Date of Submission of the demand		Date of completion of this	report					
18.10.2005		14.03.2006						
Name and mailing address of the international		Authorized Officer						
preliminary examining authority: European Patent Office			Gorald Man Call Control of the Contr					
D-80298 Munich	3656 anmu d	Morris, D	. Parag					
Tel. +49 89 2399 - 0 Tx: 523656 epmu d Fax: +49 89 2399 - 4465		Telephone No. +49 89 239	99-2182					

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

1. . .

International application No. PCT/EP2004/053448

	Box No. I	Basis of the report				
1.	With regard t	Vith regard to the language, this report is based on the international application in the language in which it was iled, unless otherwise indicated under this item.				
	which is □ interr □ publio	ort is based on translations from the original language into the following language, the language of a translation furnished for the purposes of: national search (under Rules 12.3 and 23.1(b)) cation of the international application (under Rule 12.4) national preliminary examination (under Rules 55.2 and/or 55.3)				
2.	With regard to the elements * of the international application, this report is based on (replacement sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to this report):					
	Description, F	Pages				
	1-12	as originally filed				
	Sequence listings part of the description, Pages					
	18-33	as originally filed				
	Claims, Numb	pers				
	1-7	received on 21.10.2005 with letter of 18.10.2005				
	Drawings, Sho	eets				
	1	as originally filed				
	☐ a sequer	ice listing and/or any related table(s) - see Supplemental Box Relating to Sequence Listing				
3.	☐ the de ☒ the cland the dr ☐ the se	ndments have resulted in the cancellation of: escription, pages aims, Nos. 8-14 awings, sheets/figs equence listing (specify): able(s) related to sequence listing (specify):				
4.	had not been Supplementa the de	ort has been established as if (some of) the amendments annexed to this report and listed below made, since they have been considered to go beyond the disclosure as filed, as indicated in the Box (Rule 70.2(c)). escription, pages aims, Nos. awings, sheets/figs				
	☐ the se ☐ any ta	quence listing (specify): ble(s) related to sequence listing (specify):				
	* If item	4 applies, some or all of these sheets may be marked "superseded."				

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No. PCT/EP2004/053448

J

Box No. V Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1. Statement

Novelty (N)

Yes: Claims

1-7

No: Claims

Inventive step (IS)

Yes: Claims

1-7

No: Claims

Industrial applicability (IA)

Yes: Claims
No: Claims

1-7

2. Citations and explanations (Rule 70.7):

see separate sheet

Re Item V

3

Reasoned statement under Rule 66.2(a)(ii) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1. Reference is made to the following documents:

D1: US-A-5 999 581 (BELLAOUAR ET AL) 7 December 1999 (1999-12-07)

D2: EP-A-1 353 314 (DEUTSCHE THOMSON-BRANDT GMBH) 15 October 2003 (2003-10-15)

- 2.1 D1 discloses (- cf. present independent claim 1) a device for generating [output values] (- Fig. 1) for a given value of a parameter (- "OUTPUT" Fig. 1) among N different values (- 2^(n+m) Fig. 1), whose output values can be approximated by a piecewise linear function of a variable depending on the given value (- "digital sine function and/or cosine function waveforms" col. 1, line 9 and "INPUT WORD FIW" Fig. 1), the set of N values being divided into P subsets of consecutive values (- 2^m subsets, 22 Fig. 1, "partitioned into m most significant bits" col. 2, line 47), each piece of the piecewise linear function being in a different subset.
- 2.2 In addition, D1 further discloses the device comprises corresponding features of:
 - a first memory (- 22a or 22b Fig. 1) for storing, for each subset i, a primary look-up [value] associated to a bound value of the subset i (- "stores k-bit digital samples representing amplitude points along a potion of a sine function" col. 2, lines 52-55);
 - [a second memory for storing,] for each subset i, a delta look-up [value] (- 2ⁿ Fig. 1) corresponding to the difference between a secondary look-up [value] and the primary look-up [value] related to the subset i, the secondary look-up [value] being associated to the other bound value of the subset i;
 - [..]
 - a fourth memory (- 24a or 24b Fig. 1) for storing an extrapolation coefficient (- α or β Fig. 1 and col. 2, lines 59-67) for each one of said N values, the extrapolation coefficient associated to a given value being defined in accordance with the value of a variable S for said given value and the values of the variable S for the two bound values of the subset i comprising said given value
 - (- "I-bit digital value [...] associated with one of the digital samples stored in the look-up table [22a / 22b]" col. 2, lines 61-63 and 64-66); and

in a

(Ž

- a computing block (16, 18, 30, 36, 38, 40, 50 Fig. 1) for generating [output values], for the given value in accordance with the extrapolation coefficient, primary look-up [value] and delta look-up [value]
 - (- "The multiplier 40 which receives the n-least significant bits from the 1st complement block 18 and the interpolation coefficients .alpha. and .beta., calculates the interpolation value to be added to or subtracted from the output digital sample of the sine or cosine function waveform. The logic value of the control input ctl2 to the adder/subtracter 38 determines whether the interpolation value is added to or subtracted from the digital sample to generate the intermediate digital sample. Thus, memory 24 storing the interpolation coefficients .alpha. and .beta., multiplier 40 and adder/subtracter 38 function as a linear interpolator identified generally by reference numeral 50" col. 3, lines 33-43).
- 2.3 It is acknowledged that D1 fails to disclose corresponding features of:
 - generating a look-up table;
 - primary look-up tables associated to respective bound values of a subset i;
 - a second memory for storing, for each subset i, a delta look-up table corresponding to the difference between a secondary look-up table and the primary look-up table related to the subset i, the secondary look-up table being associated to the other bound value of the subset i; or
 - a third memory for storing, for each of said N values, an index indicating which primary look-up table in the first memory and which delta look-up table in the second memory have to be used for extrapolation.

The subject-matter of claim 1 is therefore new (Article 33(2) PCT).

- 2.4 D2 discloses a method of generating a look-up table (- 13 Fig. 3, MTC LUT 133 Fig. 4) for a given value of a parameter (- AP Fig. 3) among N different values (- "256 discrete codes implemented"- para. [0058], line 4), whose output values can be approximated by a piecewise linear function of a variable
 - (- "selects the sustain table to be used [...] from about 120 sustain pulses to 1200 sustain pulses" para. [0050], lines 8-10) depending on the given value
 - (- "The control block 12 consults its internal power level [....]" para. [0050], lines 7- 10).

- 2.5 In addition, D2 also discloses a problem of the implementation of embodiment disclosed in Fig. 3 is that
 - (- "One problem of the above described implementation is the large size of the look-up tables which would be expensive to implement. In fact, for the implementation of a single metacode with the bit width as described on the above figure, 15360 bits of LUT would be required. If 256 discrete codes are implemented, 3.93 M bit of LUT data would be required." para. [0058]). wherein it is submitted that the person skilled in the art is encouraged by the disclosure of D2 to seek out solutions to the problem of providing a means for generating a look-up table for metacodes while reducing the size of the look-up tables required to generate the a different set of metacodes for each different measured value of the average power level.
- 3.1 The problem to be solved by the present invention may be regarded as how to reduce the memory required to implement a plurality of look-up tables.

The solution to this problem proposed in present claim 1 of the present application is considered as involving an inventive step (Article 33(3) PCT) for the following reasons:

- i) while D2 indicates that the problem of a large memory being required for implementing metacodes using look-up tables was known in the art, D2 neither discloses nor suggests any method for overcoming this problem;
- ii) while D1 discloses a method of overcoming a problem of requiring large look-up tables in the generation of high resolution sine or cosine function waveforms in the field of digital frequency synthesizers (- see e.g. Fig. 1 of D1 and also col. 1, lines 23-28 of D1), D1 extrapolates output values for the sine / cosine waves from single primary values of a single primary look-up table, together with values from a look-up table for storing corresponding extrapolation values. There is no suggestion or disclosure in D1, either explicit or implicit, to substitute the primary look-up values disclosed in D1, i.e. stored in look-up tables [- 22a, 22b Fig. 1 of D1] with primary look-up tables comprising a plurality of primary values.

As such therefore, the subject matter of the device claimed in respect of present independent claim 1 is considered to comprise a combination of known measures which mutually support each other to such an extent that a new technical effect is

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY (SEPARATE SHEET)

International application No.

PCT/EP2004/053448

achieved.

Accordingly, in light of PCT Guidelines 13.14(d), the subject matter of independent claim 1 is considered to involve an inventive step over a combination of the teachings of D1 and D2 within the meaning of Article 33(3) PCT.

3.2 Claims 2-7 are dependent on claim 1 and as such also meet the requirements of the PCT with respect to novelty and inventive step.

10

15

20

25

CLAIMS

- 1. Device for generating a look-up table for a given value (VAL) of a parameter (APL) among N different values, whose output values can be approximated by a piecewise linear function of a variable (S(VAL)) depending on the given value, the set of N values being divided into P subsets of consecutive values, each piece of the piecewise linear function being in a different subset, characterized in that it comprises:
- a first memory (101) for storing, for each subset i, a primary lookup table (PMTC_i) associated to a bound value of the subset i,
- a second memory (102) for storing, for each subset i, a delta look-up table corresponding to the difference between a secondary look-up table (SMTC_i) and the primary look-up table (PMTC_i) related to the subset i, the secondary look-up table (SMTC_i) being associated to the other bound value of the subset i,
- a third memory (103) for storing, for each of said N values, an index indicating which primary look-up table in the first memory (101) and which delta look-up table in the second memory (102) have to be used for extrapolation,
- a fourth memory (104) for storing an extrapolation coefficient (C) for each one of said N values, the extrapolation coefficient (C(VAL)) associated to a given value being defined in accordance with the value (S(VAL)) of a variable S for said given value (VAL) and the values (S(PMTC_i),S(SMTC_i)) of the variable S for the two bound values of the subset i comprising said given value; and
 - a computing block (105) for generating a look-up table, for the given value (VAL) in accordance with the related extrapolation coefficient (C(VAL)), primary look-up table (PMTC_i) and delta look-up table.
- 2. Device according to claim 1, characterized in that the parameter is an average power level and the variable (S(VAL)) is a number of sustain pulses corresponding to the given value (VAL) of the parameter

10

15

20

1

and that it generates a Metacode look-up table for each average power level value.

3. Device according to claim 2, characterized in that the bound level related to the primary look-up table (PMTC_i) of a subset of average power level values is the highest average power level value of the subset and the bound level related to the secondary look-up table (SMTC_i) of a subset of average power level values is the lowest average power level value of the subset.

4. Device according to one of the claims 1 to 3, characterized in that the ratio between the value (S(PMTC_i)) of the variable for one bound value in the subset i and the value (S(PMTC_{i+1})) of the variable for the same bound value in the subset i+1 equals to a fixed parameter α .

5. Device according to the claim 4, characterized in that the parameter α is defined as followed : $\alpha = \sqrt[N]{\frac{S_{MAX}}{S_{MIN}}}$

where S_{MAX} is the value of the variable (S) for a peak white image and S_{MIN} for a full white image.

6. Device according to one of the claims 1 to 5, characterized in that the extrapolation coefficient (C(VAL)) equals to :

$$C(VAL) = \frac{S(VAL) - S(PMTC_i)}{S(SMTC_i) - S(PMTC_i)}$$

- where S(PMTC_i) is the value of the variable for the highest 25 bound value of the subset i;
 - S(SMTC_i) is the value of the variable for the lowest bound value of the subset i; and
 - S(VAL) is the value of the variable for the given value.

30

15

7. Device according to one of the claims 1 to 6, characterized in that the computed look-up table equals to the sum of the output of the primary look-up table (PMTC_i) for the given value (VAL) and the output of the delta look-up table (PMTC_i) for the given value (VAL) weighted by the extrapolation coefficient for the given value (VAL).

3